

42 MODEL S32P-10 32" Multi-Touch Monitor

AN EASY- TO-INTEGRATE, ZERO BEZEL MULTI-TOUCH SOLUTION

Perfect to use in your next innovative design project or installation. Projected Capacitive touch technology provides a smooth, effortless multi-touch experience - identical to many of your favorite mobile touch devices. Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

Smooth multi-touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.



The Cutting Edge Flush Touch Monitor

KEY FEATURES AND HIGHLIGHTS

- **Projected Capacitive (P-CAP) touch technology**
- Optical in-glass technology with enhanced clarity
- Unprecedented performance - **6.5ms response time**
- Behind the bezel integration eliminates parallax issues
- Custom bezel colors and logo branding available

EASY TO DEPLOY

Plug-and-play ready monitor, and powered with 12V DC. Power adapter supplied.

SOPHISTICATED BEZEL-FREE DESIGN

Smooth touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

WIDESCREEN OR STANDARD MODELS

Multi-Touch Monitors offer a choice of 4:3 and 5:4 aspect ratios as well as 16:9 ratios in larger selected sizes.

EFFORTLESS MULTI-TOUCH EXPERIENCE

Projected capacitive touch technology provides a smooth, effortless multi-touch experience – identical to many of your favorite devices.

EXPANDED GESTURE CAPABILITY

Additional gesture software development tools and support are available to expand multi-touch functionality.

GREATER DURABILITY



Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

INSTALLATION FLEXIBILITY

VESA mount pattern or supplied edge-mounting brackets allow for flexibility when integrating the monitor into your industrial design.

WINDOWS 7 / 8/ 10 COMPATIBLE

Multi-Touch Monitors projected capacitive monitors are compatible with Windows 7, 8 and 10 by Microsoft.

42 MODEL S32P-10 32" Multi-Touch Monitor

DISPLAY DETAILS

LCD SIZE / TYPE	32.0" TFT - ACTIVE MATRIX 698.4
ACTIVE AREA	H X 392.85 V MM
BACKLIGHT	WLED
ASPECT RATIO	16:9
NATIVE RESOLUTION	1920 X 1080 FULL HD
DISPLAY COLORS	16.7 M (6 BITS + HI-FRC)
PIXEL PITCH BRIGHTNESS	0.364 H X 0.364 V MM
CONTRAST RATIO	3000:1
HOR. VIEWING ANGLE	178° (TYPICAL)
VERT. VIEWING ANGLE	178° (TYPICAL)
RESPONSE TIME	6.5 MS (TYPICAL)

TOUCH DETAILS

TOUCH TECHNOLOGY	PROJECTED CAPACITIVE
MULTI-TOUCH INPUT	10 POINTS
INPUT METHOD	FINGER, THIN GLOVE
TOUCH INTERFACE	USB-TYPE B
MULTI-TOUCH OS SUPPORT	WINDOWS 7/8/8.X AND LINUX - HID
SINGLE-TOUCH OS SUPPORT	ALL WINDOWS AND LINUX

PRODUCT DETAILS

POWER SUPPLY	100 - 240V AC
POWER CONSUMPTION	OPERATING: 65W SLEEP: 3W OFF: 1W
VIDEO INPUT	ANALOG VGA, DVI-D
AUDIO INPUT	BUILT-IN 8W / 4 CHANNEL SPEAKERS
MOUNTING OPTIONS	VESA MOUNT, OPTIONAL STAND
VESA PATTERN	400 X 200 MM
OPERATING CONDITIONS	0°C TO +40°C, NONCONDENSING 80%
AGENCY APPROVALS	TUV, CE, UL, CUL, FCC-B, ROHS, IP65
WARRANTY	3 YEAR

DIMENSIONS

DISPLAY (WXHxD)	781.5 X 476.1 X 69.7 MM
DISPLAY WEIGHT	16.8 KG