42" MULTI-TOUCH DISPLAY Specifications



MODEL S42F-10 42" Multi-Touch Monitor

AN EASY- TO-INTEGRATE, ZERO BEZEL MULTI-TOUCH SOLUTION

Perfect to use in your next innovative design project or installation. Our 42 inch touch monitor boasts an interactive experience identical to many of your favorite mobile touch devices. Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life. Refined aesthetics and cleanability.

The only interactive technology with a complete, perfect-clarity, no bezel multi-touch solution.



The Cutting Edge Flush Touch Monitor



PREMIUM TOUCH EXPERIENCE

PSD touch supports over 40 simultaneous touches with no parallax issues since the touch screen can be placed directly next to the LCD panel - zero airgap.

EXCELLENT VIEWING EXPERIENCE

PSD Touch has no sensor grid in front of the LCD screen obstructing the image quality. This ensures a superior viewing experience with maximum transparency and no image quality degradation.

RUGGED DESIGN

The robust physical characteristics maximize resistance while advanced filtering techniques ensure continued multi-touch performance despite eventual dust, liquids, or scratches. KEY FEATURES AND HIGHLIGHTS

- > Planar Scatter Detection (PSD) Touch Technology
- > Optical in-glass technology with enhanced clarity
- > Unprecedented performance 8ms response time
- > Behind the bezel integration eliminates paralax issues
- > Custom bezel colors and logo branding available

INSENSITIVE TO ELECTRONIC NOISE

Insensitive to LCD and charger noise, eliminating the need for an additional shielding layer, which adds extra cost.

OBJECT SHAPE RECOGNITION

Recreate what is happening on the surface in minute detail, providing the possibility to recognize shapes to enable for example palm rejection.

FLUSH AND SIMPLE INTEGRATION

VESA mount pattern or supplied edge-mounting brackets allow for flexibility when integrating the monitor into your industrial design.


WINDOWS 7 / 8 / 10 COMPATIBLE

Multi-Touch Monitors projected capacitive monitors are compatible with Windows 7, 8 and 10 by Microsoft.


42" MULTI-TOUCH DISPLAY Specifications




MODEL S42F-10 42" Multi-Touch Monitor 42









DISPLAY DETAILS

LCD SIZE / TYPE ACTIVE AREA BACKLIGHT ASPECT RATIO NATIVE RESOLUTION **DISPLAY COLORS PIXEL PITCH BRIGHTNESS** CONTRAST RATIO HOR. VIEWING ANGLE VERT. VIEWING ANGLE **RESPONSE TIME**

H X 523.26 V MM WLED 16:9 1920 X 1080 FULL HD 16.7 M (8 BITS) 0.485 H X 0.485 V MM 455 CD/M2 (TYPICAL) 4000:1 178° (TYPICAL) 178° (TYPICAL) 8 MS (TYPICAL)

42.0" TFT - ACTIVE MATRIX 930.24

TOUCH DETAILS

TOUCH TECHNOLOGY **MULTI-TOUCH INPUT** INPUT METHOD **TOUCH INTERFACE** MULTI-TOUCH OS SUPPORT SINGLE-TOUCH OS SUPPORT PLANAR SCATTER DETECTION **10 POINTS** FINGER, THIN GLOVE **USB-TYPE B** WINDOWS 7/8/8.X AND LINUX - NATIVE HID ALL WINDOWS AND LINUX



PRODUCT DETAILS

POWER SUPPLY	100 - 240V AC
POWER CONSUMPTION	OPERATING: 150W SLEEP: 3W OFF: 1W
VIDEO INPUT	ANALOG VGA, DVI-D, HDMI, DP
AUDIO INPUT	BUILT-IN 8W / 4 CHANNEL SPEAKERS
MOUNTING OPTIONS	VESA MOUNT
VESA PATTERN	400 X 200 MM
OPERATING CONDITIONS	0°C TO +40°C, NONCONDENSING 80%
AGENCY APPROVALS	TUV, CE, UL, CUL, FCC-B, ROHS, IP65
WARRANTY	3 YEAR

DIMENSIONS

DISPLAY (WXHXD) **DISPLAY WEIGHT**

1022.8 X 616.0 X 74.4 TBD